

TR100



ULTRA PREMIUM SHALLOW TREAD TRAILER-POSITION TIRE

- Tread design promotes even wear in free rolling/trailer axle positions.
- Center rib designed to eject stones, preserving casing integrity and promoting multiple retreads.
- $1\frac{1}{32}$ " tread depth delivers long original mileage.



| PRODUCT CODE | TIRE SIZE | PLY RATING | LOAD RANGE | LOAD INDEX | SPEED SYMBOL | OVERALL DIAM. (IN) | SECTION WIDTH (IN) | TREAD DEPTH (32NDS) | RIM | SINGLE MAX LOAD/ PRESSURE | DUAL MAX LOAD/ PRESSURE | STATIC LOAD RADIUS | REVS PER MILE | WEIGHT (LB) | TYPE |
|--------------|-------------|------------|------------|------------|--------------|--------------------|--------------------|---------------------|------|---------------------------|-------------------------|--------------------|---------------|-------------|------|
| 1133381255 | 11R22.5 | 14 | G | 144/142 | M | 41.0 | 10.9 | 14 | 8.25 | 6175lb/105psi | 5840lb/105psi | 19.5 | 500 | 113 | TL |
| 1133381256 | 11R22.5 | 16 | H | 148/145 | M | 41.0 | 10.9 | 14 | 8.25 | 6940lb/123psi | 6390lb/123psi | 19.5 | 500 | 116 | TL |
| 1133389255 | 295/75R22.5 | 14 | G | 144/141 | M | 40.2 | 11.7 | 14 | 9.00 | 6175lb/110psi | 5675lb/110psi | 18.9 | 510 | 114 | TL |
| 1133381455 | 11R24.5 | 14 | G | 146/143 | L | 42.9 | 10.9 | 14 | 8.25 | 6610lb/105psi | 6005lb/105psi | 20.8 | 476 | 124 | TL |
| 1133381456 | 11R24.5 | 16 | H | 149/146 | L | 42.9 | 10.9 | 14 | 8.25 | 7160lb/120psi | 6610lb/120psi | 20.8 | 476 | 125 | TL |
| 1133388455 | 285/75R24.5 | 14 | G | 144/141 | L | 41.1 | 11.0 | 14 | 8.25 | 6175lb/110psi | 5675lb/110psi | 19.3 | 505 | 114 | TL |